

THE NEW MACK M915 WAS DESIGNED FOR MAXIMUM PROTECTION IN THE MOST UNFORGIVING ENVIRONMENTS.

The all-new Mack Granite® M915, which uses the most advanced technologies, proudly continues the company's legendary reputation for durable and dependable trucks. From the very beginning, Mack has supported the military. During World War I, Mack built a military armored truck that aided U.S. and British troops, completing difficult tasks under very difficult conditions. They were dubbed "Bulldogs" by the British soldiers for their tenacity. From then on, the legend grew and the Mack M915 is the next in a long line of trusted and reliable trucks.



MACKGRANITE — MILITARY LINE HAUL



Engine:	MP8, non-EGR engine 13L, 480 HP, 1,800 lbft. torque JP8 fuel compatible Mack PowerLeash™ engine brake V-MAC® Engine Protection System Mack Starter Protection
Transmission:	Allison® HD 4560, 6-speed automatic transmission
Configuration:	6 x 4
Driveline:	Dana® Spicer®
Front Axle:	Mack FXL front axle Taper leaf 6600 kg (14,600 lbs) Axle forward position
Rear Axles:	Meritor® RT40-145 rear axles with inter-axle lock Mack 6-rod tandem spring suspension 18100 kg (40,000 lbs)
Brakes:	Meritor Q Plus® Bendix® 4S/4M ABS, ESP available
Air System:	Bendix System-Guard® heated air dryer
Front Tires:	12-22.5 Michelin® XZE® Central Tire Inflation (CTI) available
Rear Tires:	11-22.5 Michelin XZE Central Tire Inflation available
Frame:	9.5 mm x 300 mm x 90mm tempered steel section 460 cm (181") wheelbase 381 cm (150") platform 296 cm (116.6") front bumper to back of cab
Fifth Wheel:	Holland® FW31 no-lube, air slide

Cab:	Welded galvanized steel 150 cm (59") firewall to back of cab Bostrom® Talladega® Motion Master® Seats Tilt and telescopic adjustable steering column 2-speed electric wipers with intermittent function Heating, ventilation and air conditioning system Armor kit available
Electrical:	24V start, 12V lighting 145A alternator Hawker® Armasafe Plus batteries with battery disconnect switch Daytime running lights with override switch LED marker, clearance and taillights LED blackout lighting
Electronics:	V-MAC IV Electronic Architecture GuardDog® Active Maintenance Monitor System Road Connect™ Communication System with GPS Mack DataMax™ Fleet Management System
Electronic Communication:	SAE J1939 and SAE J1708/J1587 data buses
Collision Warning System:	Eaton® VORAD®
Fuel Capacity:	439 L (116 gallons)
Range:	1120 km (695 miles)
GVWR:	24766 kg (54,600 lbs)
GCVWR:	47627 kg (105,000 lbs)
Ground Clearance:	39 cm (15.5")
Overall Height:	287 cm (113")

Customized options available to meet mission requirements.

For more information: Mack Government/Military Office 320 King Street, Suite 301 Alexandria, VA 22314 Tel: (703) 683-7010

Fax: (703) 548-1337

