



MACK[®] MID-LINER[®]

CS
SERIES



CS 200/250P

CS 300P

CAB EQUIPMENT - ALL MODELS

ENGINE

RVI E3-190 (A-C-E)
190 H.P. @ 2500 RPM
475 lb/ft. @ 1300 RPM
Horizontal exhaust w/ catalytic converter

RVI E3-220 (A-C-E)
220 H.P. @ 2350 RPM
627 lb/ft. @ 1300 RPM
Horizontal exhaust

ELECTRICAL SYSTEM

Bosch 12V starter
Valeo 12V70A alternator
Two Delco 12V maint. free batteries,
1500 total CCA

Bosch 12V starter
Valeo 12V70A alternator
Two Delco 1110, 12V maint. free
batteries, 1500 total CCA

TRANSMISSION

Eaton 4106B, 6-speed
Clutch - 14" organic, single plate
with hydraulic control
Driveline - Dana 1610 series

RVI T1060A, 6-speed
Clutch - 15" organic, single plate
with hydraulic control
Driveline - Dana 1610 series

FRONT AXLE

FAR 8, RVI 8000 lb.
Brakes;
CS200P - Hydraulic disc, 15" diameter
CS250P - Full air S-Cam, 16.5" x 5"
Sheppard integral hydraulic power
steering
Taperleaf springs
Shock absorbers

FAR 8, RVI 8,000 lb.
Brakes; Full air S-Cam, 16.5" x 5"
Sheppard integral hydraulic power
steering
Taperleaf springs
Shock absorbers

REAR AXLE

RAR 18, 17,995 lb. capacity (CS200P)
RAR 21, 21,000 lb. capacity (CS250P)
Brakes, Full air S-Cam - 16.5" x 7"
Multileaf springs with auxiliary springs

RAH 21, 21,000 lb. capacity
Brakes, Full air S-Cam - 16.5" x 7"
Multileaf springs with auxiliary springs

FRAME

Yield Strength - 64,200 PSI
RBM - 629,160 lbs. in. per rail
Towing - Frame mounted eyes
Bumper - full width steel, flush mounted

Yield Strength - 64,200 PSI
RBM - 629,160 lbs. in. per rail
Towing - Frame mounted eyes
Bumper - full width steel, flush mounted

FUEL TANK

Steel rectangular, 55 gallon with sump

Steel rectangular, 55 gallon with sump

AIR/BRAKE SYSTEM

Air assisted hydraulic disc/air cam drum
- dual system (CS200P)
Dual air brake system (CS250P)
Air compressor, gear driven 7.0 CFM
Automatic drain valves

Dual air brake system
Air compressor, gear driven 7.0 CFM
Automatic drain valves

WHEELS/ TIRES

7.5 x 22.5 hub pilot steel disc wheels
11R22.5 14 PR tires

7.5 x 22.5 hub pilot steel disc wheels
11R22.5 14 PR tires

Conventional cab, 103" BBC

Interior Features:

Fully appointed deluxe interior

Seats; - Driver's mechanical
suspension
- Rider's 2 man bench
w/tool box

Fabric seating surfaces with vinyl trim

Three point (lap & shoulder)
seat belts

Padded door mtd. arm rests
(both doors)

Full width LH & RH padded
sun visors

Ash Tray with cigar lighter

Dome/map light
w/self-contained switch

Fresh air vent windows in door

Storage; - Storage pouch on
driver's door

- Tool box under bench seat

Gauges; oil pressure, coolant temp.,
air pressure, fuel level, speedometer/
odometer, tachometer

Exterior Features:

Fiberglass (SMC) tilt hood

Cab mounting; shock absorbers
& rubber pad

Mirrors: West Coast, Bulldog
bright finish

Safety glass tinted windows
throughout

Full opening roll-up door windows

Rectangular sealed beam headlights

Cab Finish:

Rust prevention; RVI cataphoresis
procedure

Finish coat; High gloss polyurethane

