



• MACK TRUCKS •  
**TEAM MANAGER™**





## Mack MS300PXL Terminator Specifications

<b>CAB &amp; CHASSIS:</b>	MS300PXL* four door crew cab. Gross vehicle weight rating 35,000 lbs.
<b>ENGINE:</b>	E3-220, 220 H.P. @ 2350 RPM
<b>TRANSMISSION:</b>	Allison MD3060P, automatic
<b>WHEELBASE:</b>	175"
<b>CAB TO AXLE:</b>	105"
<b>FRAME:</b>	9.1" x 2.75" x .275" main rail with .275" O.C. reinforcement, RBM 1,404,800 lbs. in.
<b>FRONT AXLE:</b>	FAR 12, 12,000 lb. capacity
<b>REAR AXLE:</b>	RAH 23, 23,000 lb. capacity
<b>RATIO:</b>	5.86 (64 mph)
<b>FUEL TANK:</b>	55 Gallon
<b>TIRES:</b>	11R22.5 (H) Michelin F: XZA R: XM+S4
<b>RIM:</b>	22.5 x 7.5" Hub pilot steel disc
<b>ALTERNATOR:</b>	Two (2) Delco 21SI, 12V100A each total 200A
<b>AIR COMPRESSOR:</b>	13.1 CFM @ 2350 RPM
<b>ENGINE BLOCK HEATER:</b>	Phillips 120V, 1500W
<b>CAB GLASS</b>	Tinted (all)
<b>MIRRORS:</b>	Bulldog Bright Finish
<b>SEATING:</b>	Seating for five (5), Four SCBA seats
<b>AIR CONDITIONING:</b>	Red Dot



## KME Firebody Terminator Specifications

<b>BODY:</b>	148 inch Streamline, all aluminum body, 1/8" material.
<b>WATER PUMP:</b>	Hale 1250 GPM, single stage
<b>WATER TANK:</b>	1,000 gallon UPF Poly IIE
<b>HOSEBED:</b>	Seventy four (74) cubic feet
<b>LADDERS:</b>	Twenty four (24) and fourteen (14) feet
<b>COMPARTMENTS:</b>	Left side high side Transverse rear step
<b>HOSES:</b>	Two (2) six (6) inch hard suction hoses Two (2) 1 3/4" crosslays Five (5) 2 1/2" discharges Three (3) inch deck gun discharges  Spare air bottle storage in body fenders.  All NFPA required emergency lighting.  Many more options available .

### KME Fire Apparatus

One Industrial Complex  
Nesquehoning, PA 18240  
Telephone: 717-669-5132  
800-235-3928  
Fax: 717-645-7007

