

OPTIONAL EQUIPMENT • B1400L & B5400L Series

ENGINE	ENGINE MODEL	DISC & CHASSIS	NO. OF DISC.	HP (CV) IN	HP (CV) OUT	MAX. TORQUE (kg-cm)
L20	BL-2-2000L	4.7" x 4.7"	9.0	11.0	20.0 (27.0)	48.0 (3.0)
L30	BL-2-3000L	4.7" x 5.7"	9.0	13.0	23.0 (31.0)	57.0 (3.5)
L50	BL-2-5000L	5.7" x 5.7"	9.0	15.0	25.0 (33.0)	67.0 (4.0)
L70	BL-2-7000L	5.7" x 6.7"	9.0	17.0	27.0 (36.0)	75.0 (4.5)
D1-20	BL-2-2000L	5.7" x 5.7"	1	11.0	22.0 (29.0)	60.0 (3.8)

WHEELBASE..... 30", 34", 37", 40"

See chart above for wheelbase info.

*All wheel combinations shown elsewhere may be available. Contact factory.

FRONT AXLE

1 axle disc (standard)	2.00 lb. axle
1 axle disc (optional)	2.50 lb. axle
1 front disc (L20, L30, L50)	3.00 lb. axle
1 rear disc (L20, L30, L50)	3.00 lb. axle
1 front disc (L70)	3.50 lb. axle
1 rear disc (L70)	3.50 lb. axle

AXLE TIRING..... (optional) Standard Non-Standard

WHEELS

FRONT	27" x 26" 255 95 HO
FRONT	26" x 26" 255 95 HO
FRONT	27" x 26" 255 95 HO
REAR	27" x 26" 255 95 HO
REAR	27" x 26" 255 95 HO
REAR	27" x 26" 255 95 HO
REAR	27" x 26" 255 95 HO

SPRINGS

1.50 lb. is price of standard 1.50 lb.
1.70 lb. is price of standard 1.70 lb.

CLUTCH

2.00..... 20" clutch, large spring (all 40" & 42")

TRANSMISSIONS

200	2 spd., steel
300	3 spd., steel
500	3 spd., steel
700	3 spd., steel

GEAR OIL..... 500 LBS. Capacity (200, 300, 500, 700) Series..... 4.0, 4.5, 5.0

(See chart above)

ELECTRICAL SYSTEM

Electric	27 watt
Electric	Two 27 watt, 20 amp
12" x 18" Current Engine	

DISC WEIGHT & TIRE

1.5 Disc	(See chart above for pricing)
2.5 Disc	2.00 (2.5)
3.5 Disc	2.50 (3.0)

TRACTOR PACKAGE: (As Applied) (See chart above, front wheel, front wheel, rear wheel, front wheel, front wheel, 17" air hose, 1 small electrical junction block, 17" wire, 17" electrical cable and 17" tire plug.
(Available 17" in water discharge or battery cable)

2000 (Standard)	2.00
27" (200)	2.00
27" (300)	2.00
27" (500)	2.00


These tires available in standard sizes, with standard 17" air hose.

*All wheel combinations of front wheel, standard wheel, rear wheel, standard wheel, 17" air hose.

OPTIONAL EQUIPMENT

17" Water Hose	1.00 (1.50)
17" Air Hose	1.00 (1.50)
17" Water, 17" Air	1.00 (1.50)
17" Water, 17" Air	1.00 (1.50)

1.00 (1.50) (Standard)
1.00 (1.50) (Standard)
1.00 (1.50) (Standard)
1.00 (1.50) (Standard)



Specifications subject to change without notice. Illustrations are not necessarily a representation of standard specifications.

**BU-400L
or
KS-400L**
CHASSIS DIMENSIONS

WB	CA	CL	DL	TURNING CIRCLE DIA. (Outer Edge of Tire) ESTIMATED	
				RIGHT	LEFT
127"	142"	97"	127"	67'	67'
139"	154"	89"	139"	67'	67'
151"	166"	81"	151"	67'	67'
163"	178"	73"	163"	67'	67'
175"	190"	65"	175"	67'	67'

TRUCK WEIGHT	ON DUMMIES		ON		OFF	
	EMPTY	LOADED	EMPTY	LOADED	MAX. W.	B. IN.
10,000 LB.	10.0	10.0	10.0	10.0	10.0	10.0
12,000 LB.	10.0	10.0	10.0	10.0	10.0	10.0
14,000 LB.	10.0	10.0	10.0	10.0	10.0	—
16,000 LB.	10.0	10.0	10.0	10.0	10.0	—

Frame heights are subject to variations: 1/2" empty, 1/4" loaded.