

**GREATER DANGER DEMANDS NEED
GREATER RESPONSE.**

Striker

3000

Your world is ARFF. Your responsibility has reached an all-new extreme. You have to lead like never before. The new Striker changes everything. Greater fire suppression, control, safety and versatility maximize your response like no other truck in the industry. Arming you with the ultimate attack force, for the ultimate threats.

FOLLOW NO ONE.



NEW STRIKER STANDARDS

The new Striker delivers innovative fire suppression, unmatched chassis performance, advanced safety systems, unsurpassed reliability and durability and smart design. So you can take on ARFF hazards like never before.

Innovative Fire Suppression

- Optional Pulse Technology casts dry chemical powder over 90 ft. (27 m), 3 times the current capacity
- Optional increased pump capacity
- Optional crosslays to access handlines from either side of the truck

Unmatched Chassis Performance

- More than 2,000 lbs. (907 kg) lighter than the current Striker for faster acceleration
- 0-50 mph (80 kph) in under 35 seconds
- Comes equipped with Oshkosh® patented TAK-4® all-wheel independent suspension
- Center steer for greater all-around visibility

Advanced Safety Systems

- Improved turning radius and maneuverability
- 11% greater braking power over the current Striker (with disc brake option)
- 84 sq. ft. glass for maximum driver visibility

Unsurpassed Reliability and Durability

- Walk-in service port with incorporated drip pan
- Industry-leading access to engine and power pack
- 29% greater fuel capacity
- 24/7/365 support

Smart Design

- Indicator lighting clearly identifies controls (water, foam, clean agent)
- Cab space – 275 cubic ft. (7.8 cubic m)

THE NEW STRIKER CHANGES THE WAY YOU FIGHT BACK.

Striker

3000

oshkoshairport.com

+1 920 235 9151



* Partial options listing only; additional and special request options are also available.

The Striker 3000 meets or exceeds all National Fire Protection Association (NFPA) 414, Federal Aviation Administration (FAA) and International Civil Aviation Organization (ICAO) requirements for all 3,000 gallon (11356 l) water capacity ARFF vehicles.

PERFORMANCE

Top Speed: Greater than 70 mph (113 km/h)

Side Slope Stability (Static): $\geq 30^\circ$

Gradeability: Ascend/descend a 50% grade

Turning Diameter: 78 ft. (23.8 m)

Dimensions:

- Length – 475 in. (1207 cm)
- U.S. Width – 120 in. (305 cm)
- European Width – 118 in. (300 cm)
- Height without HRET – Less than or equal to 140 in. (356 cm) (with full water tank)

CHASSIS

Engine: Deutz TCD 16.0 L V8 with 2,131 ft./lbs. of torque at 1,400 rpm

700 hp Tier 4i / Euro 5 emissions compliant

Transmission: Allison 4800 EVS transmission; electronic / 7-speed / automatic

Anti-Lock Braking System (ABS)

Cab: 5-person seating; aluminum frame construction with center steering position; wrap-around, cockpit style instrument panel; easy-read backlit gauges and controls

Transfer Case: Oshkosh® independent with torque proportioning differential and driver selected locking mechanism

Front Axle: 31,000 lbs. (14,061 kg); Oshkosh double reduction with bevel gear differential; driver operated differential lock (transverse and separate front to back)

Front Brakes: Drum brakes standard (Rockwell® Dual Actuator Air); optional disc brakes available (17" Rotor Bendix® SN7 sliding caliper)

Rear Axles: 31,000 lbs. (14,061 kg) and 62,000 lbs. (28,123 kg); Oshkosh double reduction with bevel gear differential; driver operated differential lock

Rear Brakes: S-cam type; air/drum brake standard, disc brake available

Suspension: Oshkosh TAK-4® independent system with dual control arms and single coil spring; up to 16 in. (40.6 cm) of wheel end travel with superior all-terrain mobility, ride quality and handling


Air Conditioning: 60,000 BTU cooling capacity

Heat: 80,000 BTU heating capacity

Tires: Michelin® 24R21 XZL

GVWR: 87,000 lbs. (39,463 kg)

Wheelbase: 267 in. (678 cm) from Axle 1 to Axle 3



FIREFIGHTING SYSTEM

Roof Turret: Non-aspirating and aspirating options available, electric joystick control; 625/1,250 gpm (2366/4732 lpm), options available up to 1,585 gpm (6000 lpm)

Bumper Turret: Non-aspirating, electric joystick control; 300 gpm (1136 lpm), higher flow options available

Water Tank: 3,000 gal. (11356 l) capacity; corrosion and UV resistant polypropylene; optional 12000 and 12500 l

Foam Tank: 420 gal. (1590 l) capacity; corrosion and UV resistant polypropylene

Fire Pump: Power divider driven Waterous® CRQB; single stage centrifugal, cast iron body, brass impeller, stainless steel shaft, pump-and-roll capable; 2,000 gpm (7511 lpm)

- Optional Waterous CRUQB High Flow Pump – 2,650 gpm (10,031 lpm)

- Optional Brass/Bronze Pump

Fixed hose reels: 100 ft. (30 m) Hose Length Bundled with Water/Foam or

150 ft. (46 m) Hose with Dry Chemical

Foam Proportioning System Around the Pump

Advanced Firefighting Technology Ready

- Ultra High Pressure Water
- High Pressure Water
- Quad Agent (Water, Foam, Dry Chemical, Clean Agent)
- Compressed Air Foam System

OPTIONS*

Pulse Technology

- Casts Dry Chemical Powder "Dry" over 90 ft. (27 m)
- Trouble-Free Delivery from the Storage Tank
- Eliminates Routine Dry Chemical Tank Fluffing

Swing Out Hose Reels: 100 ft. (30 m) Hose Length Bundled with Water/Foam or

150 ft. (46 m) Hose with Dry Chemical

Crosslays: Up to 2 crosslays with up to 300 ft (91 m) of 1.75 in. (44 mm) hose per crosslay with 2 preconnects (1 each side).

Disc Brakes (outboard mounted)

Mechanical Rear Axle Steering

Central Tire Inflation

Winterization System: For temperatures extreme as -40° F/C

Hydraulic Generator: 10kW or 15kW options

Auxiliary Lighting

High Reach Extendable Turret (HRET)

High Volume, Fixed Mount or Low Attack Bumper Turrets: 1,250 gpm (4732 lpm) capacity

Dry Chemical System: Single agent or dual agent handline and/or primary turret discharge capability

Central Lube System

Hydro-Chem™ Direct Injection: Dry chemical nozzle for primary turret and/or dual agent handline discharge

Clean Agent System: Single agent or dual agent handline, and/or HRET discharge capability

Electronic Foam Proportioning